

FLEMING RANGE

Oil-Less Belt Driven Scroll Compressors

MODEL	Pressure		F.A.D.		rpm	Power kW / Hp	Noise dB	Tank L	Weight Kg	Dimensions LxWxH (mm)
	bar max	PSI max	L/min	CFM						
FLEMING OPEN 2,2/200	8	116	240	8,5	3250	2,2 / 3	70	200	109	1400x550x970
	10	145	200	7,1	2870					
FLEMING OPEN 3,7/270	8	116	420	15	2200	3,7 / 5	74	270	157	1640x650x1035
FLEMING OPEN 5,5/270	8	116	630	22,5	3180	5,5 / 7,5	76		157	1640x650x1035
	10	145	520	18,5	2650					
FLEMING OPEN 5,5/470	8	116	630	22,5	3180			470	202	2200x650x1105
	10	145	520	18,5	2650					
FLEMING 2,2	8	116	240	8,5	3250	2,2 / 3	64	25	97	700x650x890
	10	145	200	7,1	2870		63			
FLEMING 2,2/200	8	116	240	8,5	3250		64	200	155	1400x530x1240
	10	145	200	7,1	2870		63			
FLEMING 3,7	8	116	410	15	2200	3,7 / 5	67	10	150	700x650x890
FLEMING 3,7/270							67	270	240	1550x650x1550
FLEMING 5,5	8	116	630	22,5	3180	5,5 / 7,5	69	10	160	1550x650x890
	10	145	520	18,5	2650		68			
FLEMING 5,5/270	8	116	630	22,5	3180		69	270	245	1550x650x1550
	10	145	520	18,5	2650		68			
FLEMING 5,5/470	8	116	630	22,5	3180		69	470	280	1900x650x1620
	10	145	520	18,5	2650		68			
FLEMING 7.5	8	116	410-840	14,3-22,6	2440	2x3,7 / 2x5,5	67	--	265	1160x597x1034
	10	145	200-720	7,1-25,4	2870-2650	2,2+5,5 / 3+7,5	67			
FLEMING 7.5/270	8	116	410-840	14,3-22,6	2440	2x3,7 / 2x5,5	67	270	350	1582x597x1556
	10	145	200-720	7,1-25,4	2870-2650	2,2+5,5 / 3+7,5	67			
FLEMING 7.5/470	8	116	410-840	14,3-22,6	2440	2x3,7 / 2x5,5	67	470	380	1992x600x1670
	10	145	200-720	7,1-25,4	2870-2650	2,2+5,5 / 3+7,5	67			
FLEMING 11	8	116	630-1260	22,5-44,5	3180	2x5,5 / 2x7,5	67	--	275	1160x597x1034
	10	145	520-1040	18,5-36,7	2650	2x5,5 / 2x7,5	67			
FLEMING 11/270	8	116	630-1260	22,5-44,5	3180	2x5,5 / 2x7,5	67	270	360	1582x597x1556
	10	145	520-1040	18,5-36,7	2650	2x5,5 / 2x7,5	67			
FLEMING 11/470	8	116	630-1260	22,1-44,5	3180	2x5,5 / 2x7,5	67	470	390	1992x600x1670
	10	145	520-1040	18,5-36,7	2650	2x5,5 / 2x7,5	67			
FLEMING 15	8	116	630-1890	22,5-66,7	3180	3x5,5 / 3x7,5	67	--	515	1410x800x1500
	10	145	520-1560	18,5-55,1	2650	3x5,5 / 3x7,5	67			
FLEMING 18.5	8	116	410-2100	14,4-74,1	3180	2x3,7 + 2x5,5 / 2x5,5 + 2x7,5	68	--	570	1410x800x1500
	10	145	200-1760	7,1-62,1	2650	2,2 + 3x5,5 / 3 + 3x7,5	68			
FLEMING 22	8	116	630-2520	22,5-88,9	3180	4x5,5 / 4x7,5	69	--	580	1410x800x1500
	10	145	520-2080	18,5-73,4	2650	4x5,5 / 4x7,5	69			

Reference conditions: Intake air temperature 20°C (68°F) - atmospheric pressure 1 bar (14,5 psig).
The air flow rates are measured at the following working pressures: 7,5 bar for models at 8 bar - 9,5 bar for models at 10 bar.
The data and performances in accordance with ISO 1217 directives. Sound level measured in accordance with PNEUROP/CAGI standards.

Models from 7,5 to 22 optional dryer is available on request.

