

G-TEC 7.5 - 11 - 15 kW

- Power range from 7.5 kW to 11 kW;
- Operating pressure at 8-10-13 bar;
- 270 or 500-lt air receiver;
- Fully integrated refrigerated dryer and dual oil removing filters;
- Operating noise level between 62 and 65 dB(A);
- Variable speed version (11 kW).



▲ G-TEC 15-10-270 DF



▲ G-TEC 15-10-500 DF DV

Model	Tank	Power		Air delivered **			Max. Pressure		Sound level	Connection	Net Weights		Net Dimensions L x W x H
	lt	kW	HP	l/min.	m³/h	CFM	bar	p.s.i.	dB(A)	G	Kg	Lbs	(cm)
FIXED SPEED DRIVE													
G-TEC 7.5-08-270 DF	270	7.5	10	1250	75	44	8	116	62	3/4"	326	719	156 x 70 x 158
G-TEC 7.5-10-270 DF	270	7.5	10	1000	60	35	10	145	62	3/4"	326	719	156 x 70 x 158
G-TEC 7.5-13-270 DF	270	7.5	10	750	45	26	13	188	62	3/4"	336	741	156 x 70 x 158
G-TEC 7.5-08-500 DF	500	7.5	10	1250	75	44	8	116	62	3/4"	386	851	198 x 70 x 167
G-TEC 7.5-10-500 DF	500	7.5	10	1000	60	35	10	145	62	3/4"	386	851	198 x 70 x 167
G-TEC 7.5-13-500 DF	500	7.5	10	750	45	26	13	188	62	3/4"	401	884	198 x 70 x 167
G-TEC 11-08-270 DF	270	11	15	1650	99	58	8	116	65	3/4"	350	772	156 x 70 x 158
G-TEC 11-10-270 DF	270	11	15	1500	90	53	10	145	65	3/4"	350	772	156 x 70 x 158
G-TEC 11-13-270 DF	270	11	15	1150	69	41	13	188	65	3/4"	360	794	156 x 70 x 158
G-TEC 11-08-500 DF	500	11	15	1650	99	58	8	116	65	3/4"	410	904	198 x 70 x 167
G-TEC 11-10-500 DF	500	11	15	1500	90	53	10	145	65	3/4"	410	904	198 x 70 x 167
G-TEC 11-13-500 DF	500	11	15	1150	69	41	13	188	63	3/4"	425	937	198 x 70 x 167
G-TEC 15-08-270 DF	270	15	20	2150	129	76	8	116	65	3/4"	376	829	156 x 70 x 158
G-TEC 15-10-270 DF	270	15	20	1850	111	65	10	145	65	3/4"	376	829	156 x 70 x 158
G-TEC 15-13-270 DF	270	15	20	1550	93	55	13	188	65	3/4"	386	851	156 x 70 x 158
G-TEC 15-08-500 DF	500	15	20	2150	129	76	8	116	65	3/4"	436	961	198 x 70 x 167
G-TEC 15-10-500 DF	500	15	20	1850	111	65	10	145	65	3/4"	436	961	198 x 70 x 167
G-TEC 15-13-500 DF	500	15	20	1550	93	55	13	188	64	3/4"	451	994	198 x 70 x 167
VARIABLE SPEED DRIVE (DV)													
G-TEC 11-08-270 DF DV	270	11	15	1650 / 660	99 / 40	58 / 23	8	116	65	3/4"	366	807	156 x 70 x 158
G-TEC 11-10-270 DF DV	270	11	15	1500 / 600	90 / 36	53 / 21	10	145	65	3/4"	366	807	156 x 70 x 158
G-TEC 11-13-270 DF DV	270	11	15	1150 / 460	69 / 28	41 / 16	13	188	65	3/4"	398	878	156 x 70 x 158
G-TEC 11-08-500 DF DV	500	11	15	1650 / 660	99 / 40	58 / 23	8	116	65	3/4"	428	944	198 x 70 x 167
G-TEC 11-10-500 DF DV	500	11	15	1500 / 600	90 / 36	53 / 21	10	145	65	3/4"	428	944	198 x 70 x 167
G-TEC 11-13-500 DF DV	500	11	15	1150 / 460	69 / 28	41 / 16	13	188	65	3/4"	457	1008	198 x 70 x 167

Free air delivery as per ISO 1217 Annex C, at 7.5 - 9.5 - 12.5 bar at the compressor outlet. ± 3 dB (A) as PNEUROP/CAGI PN-NTC 2.3.

G-TEC 18.5 - 22 kW

- Power range of 18.5 and 22 kW;
- Operating pressure at 8-10-13 bar;
- 500-lt air receiver;
- Fully integrated refrigerated dryer and dual oil removing filters;
- Operating noise level between 70 and 71 dB(A);
- Variable speed versions (only 22 kW models).



▲ G-TEC 18.5-10-500 DF



▲ G-TEC 22-10-500 DF DV

Model	Tank		Power		Air delivered **			Max. Pressure		Sound level	Connection	Net Weights		Net Dimensions L x W x H
	lt		kW	HP	l/min.	m³/h	CFM	bar	p.s.i.	dB(A)	G	Kg	Lbs	(cm)
FIXED SPEED DRIVE														
G-TEC 18.5-08-500 DF	500		18.5	25	2700	162	95	8	116	70	3/4"	595	1312	198 x 73 x 175
G-TEC 18.5-10-500 DF	500		18.5	25	2500	150	88	10	145	70	3/4"	595	1312	198 x 73 x 175
G-TEC 18.5-13-500 DF	500		18.5	25	2050	123	72	13	188	70	3/4"	627	1382	198 x 73 x 175
G-TEC 22-08-500 DF	500		22	30	3350	201	118	8	116	71	3/4"	615	1356	198 x 73 x 175
G-TEC 22-10-500 DF	500		22	30	3000	180	106	10	145	71	3/4"	615	1356	198 x 73 x 175
G-TEC 22-13-500 DF	500		22	30	2400	144	85	13	188	71	3/4"	647	1426	198 x 73 x 175
VARIABLE SPEED DRIVE (DV)														
G-TEC 22-08-500 DF DV	500		22	30	3350 / 1340	201 / 80	118 / 47	8	116	71	3/4"	650	1433	198 x 73 x 175
G-TEC 22-10-500 DF DV	500		22	30	3000 / 1200	180 / 72	106 / 42	10	145	71	3/4"	650	1433	198 x 73 x 175
G-TEC 22-13-500 DF DV	500		22	30	2400 / 960	144 / 58	85 / 34	13	188	71	3/4"	682	1503	198 x 73 x 175

Free air delivery as per ISO 1217 Annex C, at 7.5 - 9.5 - 12.5 bar at the compressor outlet. ± 3 dB (A) as PNEUROP/CAGI PN-NTC 2.3.

** For DV models the data refer to max. and min. values

G-TEC BELT-DRIVEN ROTARY SCREW AIR STATION

LESS...

- SPACE
- ENERGY
- NOISE

...MORE

- CONVENIENT
- FEATURES
- PERFORMANCE