



▲ PASCAL 7.5-10



▲ PASCAL 5.5-10 DF



▲ PASCAL 7.5-10-270



▲ PASCAL 7.5-10-270 DF

PASCAL 2.2 - 7.5 kW

Model	Code	Tank	Power		Air delivered			Max. Pressure		Sound level	Connection	Net Weights		Net Dimensions L x W x H
		lt	kW	HP	m³/min.	m³/h	CFM	bar	p.s.i.	dB(A)	G	Kg	Lbs	(cm)
FLOOR MOUNTED														
PASCAL 2.2-08	V60TK72PWS280	—	2.2	3	0.33	19.5	11.5	8	116	58	1/2"	160	353	86 x 65 x 85
PASCAL 2.2-10	V60TR72PWS280	—	2.2	3	0.29	17.4	10.2	10	145	58	1/2"	160	353	86 x 65 x 85
PASCAL 3.0-08	V60TI72PWS280	—	3	4	0.43	25.8	15.2	8	116	59	1/2"	164	362	86 x 65 x 85
PASCAL 3.0-10	V60TS72PWS280	—	3	4	0.39	23.1	13.6	10	145	59	1/2"	164	362	86 x 65 x 85
PASCAL 4.0-08	V60TQ92PWS280	—	4	5.5	0.58	34.8	20.5	8	116	60	1/2"	165	364	86 x 65 x 85
PASCAL 4.0-10	V60TT92PWS280	—	4	5.5	0.49	29.1	17.1	10	145	60	1/2"	165	364	86 x 65 x 85
PASCAL 5.5-08	V60TF92PWS280	—	5.5	7.5	0.72	43.2	25.4	8	116	64	1/2"	167	368	86 x 65 x 85
PASCAL 5.5-10	V60TU92PWS280	—	5.5	7.5	0.65	39	22.9	10	145	64	1/2"	167	368	86 x 65 x 85
PASCAL 7.5-08	V60TG92PWS280	—	7.5	10	1.25	75	44.1	8	116	66	1/2"	182	401	86 x 65 x 85
PASCAL 7.5-10	V60TV92PWS280	—	7.5	10	1.00	60	35.3	10	145	66	1/2"	182	401	86 x 65 x 85
PASCAL 7.5-13	V60TH92PWS280	—	7.5	10	0.75	45	26.5	13	188	66	1/2"	182	401	86 x 65 x 85
FLOOR MOUNTED WITH DRYER (DF)														
PASCAL 2.2-08 DF	V60TK72PWS380	—	2.2	3	0.33	19.5	11.5	8	116	58	1/2"	187	412	117 x 65 x 85
PASCAL 2.2-10 DF	V60TR72PWS380	—	2.2	3	0.29	17.4	10.2	10	145	58	1/2"	187	412	117 x 65 x 85
PASCAL 3.0-08 DF	V60TI72PWS380	—	3	4	0.43	25.8	15.2	8	116	59	1/2"	191	421	117 x 65 x 85
PASCAL 3.0-10 DF	V60TS72PWS380	—	3	4	0.39	23.1	13.6	10	145	59	1/2"	191	421	117 x 65 x 85
PASCAL 4.0-08 DF	V60TQ92PWS380	—	4	5.5	0.58	34.8	20.5	8	116	60	1/2"	192	423	117 x 65 x 85
PASCAL 4.0-10 DF	V60TT92PWS380	—	4	5.5	0.49	29.1	17.1	10	145	60	1/2"	192	423	117 x 65 x 85
PASCAL 5.5-08 DF	V60TF92PWS380	—	5.5	7.5	0.72	43.2	25.4	8	116	64	1/2"	194	428	117 x 65 x 85
PASCAL 5.5-10 DF	V60TU92PWS380	—	5.5	7.5	0.65	39	22.9	10	145	64	1/2"	194	428	117 x 65 x 85
PASCAL 7.5-08 DF	V60TG92PWS380	—	7.5	10	1.25	75	44.1	8	116	66	1/2"	209	461	117 x 65 x 85
PASCAL 7.5-10 DF	V60TV92PWS380	—	7.5	10	1.00	60	35.3	10	145	66	1/2"	209	461	117 x 65 x 85
PASCAL 7.5-13 DF	V60TH92PWS380	—	7.5	10	0.75	45	26.5	13	188	66	1/2"	209	461	117 x 65 x 85
WITH TANK														
PASCAL 2.2-08-270	V91TK72PWS280	270	2.2	3	0.33	19.5	11.5	8	116	58	1/2"	241	531	120 x 65 x 154
PASCAL 2.2-10-270	V91TR72PWS280	270	2.2	3	0.29	17.4	10.2	10	145	58	1/2"	241	531	120 x 65 x 154
PASCAL 3.0-08-270	V91TI72PWS280	270	3	4	0.43	25.8	15.2	8	116	59	1/2"	245	540	120 x 65 x 154
PASCAL 3.0-10-270	V91TS72PWS280	270	3	4	0.39	23.1	13.6	10	145	59	1/2"	245	540	120 x 65 x 154
PASCAL 4.0-08-270	V91TQ92PWS280	270	4	5.5	0.58	34.8	20.5	8	116	60	1/2"	246	542	120 x 65 x 154
PASCAL 4.0-10-270	V91TT92PWS280	270	4	5.5	0.49	29.1	17.1	10	145	60	1/2"	246	542	120 x 65 x 154
PASCAL 5.5-08-270	V91TF92PWS280	270	5.5	7.5	0.72	43.2	25.4	8	116	64	1/2"	248	547	120 x 65 x 154
PASCAL 5.5-10-270	V91TU92PWS280	270	5.5	7.5	0.65	39	22.9	10	145	64	1/2"	248	547	120 x 65 x 154
PASCAL 7.5-08-270	V91TG92PWS280	270	7.5	10	1.25	75	44.1	8	116	66	1/2"	262	578	120 x 65 x 154
PASCAL 7.5-10-270	V91TV92PWS280	270	7.5	10	1.00	60	35.3	10	145	66	1/2"	262	578	120 x 65 x 154
PASCAL 7.5-13-270	V91TH92PWS280	270	7.5	10	0.75	45	26.5	13	188	66	1/2"	292	644	120 x 65 x 154
PASCAL 7.5-08-500	V83TG92PWS280	500	7.5	10	1.25	75	44.1	8	116	66	1/2"	304	670	200 x 65 x 150
PASCAL 7.5-10-500	V83TV92PWS280	500	7.5	10	1.00	60	35.3	10	145	66	1/2"	304	670	200 x 65 x 150
PASCAL 7.5-13-500	V83TH92PWS280	500	7.5	10	0.75	45	26.5	13	188	66	1/2"	337	743	200 x 65 x 150
WITH TANK AND DRYER (DF)														
PASCAL 2.2-08-270 DF	V91TK72PWS380	270	2.2	3	0.33	19.5	11.5	8	116	58	1/2"	268	591	120 x 65 x 154
PASCAL 2.2-10-270 DF	V91TR72PWS380	270	2.2	3	0.29	17.4	10.2	10	145	58	1/2"	268	591	120 x 65 x 154
PASCAL 3.0-08-270 DF	V91TI72PWS380	270	3	4	0.43	25.8	15.2	8	116	59	1/2"	272	600	120 x 65 x 154
PASCAL 3.0-10-270 DF	V91TS72PWS380	270	3	4	0.39	23.1	13.6	10	145	59	1/2"	272	600	120 x 65 x 154
PASCAL 4.0-08-270 DF	V91TQ92PWS380	270	4	5.5	0.58	34.8	20.5	8	116	60	1/2"	273	602	120 x 65 x 154
PASCAL 4.0-10-270 DF	V91TT92PWS380	270	4	5.5	0.49	29.1	17.1	10	145	60	1/2"	273	602	120 x 65 x 154
PASCAL 5.5-08-270 DF	V91TF92PWS380	270	5.5	7.5	0.72	43.2	25.4	8	116	64	1/2"	275	606	120 x 65 x 154
PASCAL 5.5-10-270 DF	V91TU92PWS380	270	5.5	7.5	0.65	39	22.9	10	145	64	1/2"	275	606	120 x 65 x 154
PASCAL 7.5-08-270 DF	V91TG92PWS380	270	7.5	10	1.25	75	44.1	8	116	66	1/2"	289	637	120 x 65 x 154
PASCAL 7.5-10-270 DF	V91TV92PWS380	270	7.5	10	1.00	60	35.3	10	145	66	1/2"	289	637	120 x 65 x 154
PASCAL 7.5-13-270 DF	V91TH92PWS380	270	7.5	10	0.75	45	26.5	13	188	66	1/2"	317	699	120 x 65 x 154
PASCAL 7.5-08-500 DF	V83TG92PWS380	500	7.5	10	1.25	75	44.1	8	116	66	1/2"	339	747	200 x 65 x 150
PASCAL 7.5-10-500 DF	V83TV92PWS380	500	7.5	10	1.00	60	35.3	10	145	66	1/2"	339	747	200 x 65 x 150
PASCAL 7.5-13-500 DF	V83TH92PWS380	500	7.5	10	0.75	45	26.5	13	188	66	1/2"	372	820	200 x 65 x 150



PASCAL 11 - 15 kW

Model	Code	Tank	Power		Air delivered			Max. Pressure		Sound level	Connection	Net Weights		Net Dimensions L x W x H
		lt	kW	HP	m³/min.	m³/h	CFM	bar	p.s.i.	dB(A)	G	Kg	Lbs	(cm)
FLOOR MOUNTED														
PASCAL 11-08	V60TM92PWS280	–	11	15	1.65	99	58.2	8	116	69	3/4"	228	503	104 x 70 x 100
PASCAL 11-10	V60TX92PWS280	–	11	15	1.50	90	53.0	10	145	69	3/4"	228	503	104 x 70 x 100
PASCAL 11-13	V60TN92PWS280	–	11	15	1.15	69	40.6	13	188	69	3/4"	228	503	104 x 70 x 100
PASCAL 15-08	V60TY92PWS280	–	15	20	2.15	129	75.9	8	116	70	3/4"	238	525	104 x 70 x 100
PASCAL 15-10	V60TZ92PWS280	–	15	20	1.85	111	65.3	10	145	70	3/4"	238	525	104 x 70 x 100
PASCAL 15-13	V60TP92PWS280	–	15	20	1.55	93	54.7	13	188	70	3/4"	238	525	104 x 70 x 100
FLOOR MOUNTED WITH DRYER (DF)														
PASCAL 11-08 DF	V60TM92PWS380	–	11	15	1.65	99	58.2	8	116	69	3/4"	280	617	140 x 70 x 100
PASCAL 11-10 DF	V60TX92PWS380	–	11	15	1.50	90	53.0	10	145	69	3/4"	280	617	140 x 70 x 100
PASCAL 11-13 DF	V60TN92PWS380	–	11	15	1.15	69	41	13	188	69	3/4"	280	617	140 x 70 x 100
PASCAL 15-08 DF	V60TY92PWS380	–	15	20	2.15	129	75.9	8	116	70	3/4"	290	639	140 x 70 x 100
PASCAL 15-10 DF	V60TZ92PWS380	–	15	20	1.85	111	65.3	10	145	70	3/4"	290	639	140 x 70 x 100
PASCAL 15-13 DF	V60TP92PWS380	–	15	20	1.55	93	54.7	13	188	70	3/4"	290	639	140 x 70 x 100
WITH TANK														
PASCAL 11-08-270	V91TM92PWS280	270	11	15	1.65	99	58.2	8	116	69	3/4"	300	662	155 x 70 x 153
PASCAL 11-10-270	V91TX92PWS280	270	11	15	1.50	90	53	10	145	69	3/4"	300	662	155 x 70 x 153
PASCAL 11-13-270	V91TN92PWS280	270	11	15	1.15	69	40.6	13	188	69	3/4"	328	723	155 x 70 x 153
PASCAL 11-08-500	V83TM92PWS280	500	11	15	1.65	99	58.2	8	116	69	3/4"	402	886	200 x 70 x 165
PASCAL 11-10-500	V83TX92PWS280	500	11	15	1.50	90	53	10	145	69	3/4"	402	886	200 x 70 x 165
PASCAL 11-13-500	V83TN92PWS280	500	11	15	1.10	66	38.83	13	188	69	3/4"	435	959	200 x 70 x 165
PASCAL 15-08-270	V91TY92PWS280	270	15	20	2.15	129	75.9	8	116	70	3/4"	310	684	155 x 70 x 153
PASCAL 15-10-270	V91TZ92PWS280	270	15	20	1.85	111	65.3	10	145	70	3/4"	310	684	155 x 70 x 153
PASCAL 15-13-270	V91TP92PWS280	270	15	20	1.55	93	54.7	13	188	70	3/4"	338	745	155 x 70 x 153
PASCAL 15-08-500	V83TY92PWS280	500	15	20	2.15	129	75.9	8	116	70	3/4"	412	908	200 x 70 x 165
PASCAL 15-10-500	V83TZ92PWS280	500	15	20	1.85	111	65.3	10	145	70	3/4"	412	908	200 x 70 x 165
PASCAL 15-13-500	V83TP92PWS280	500	15	20	1.55	93	54.7	13	188	70	3/4"	445	981	200 x 70 x 165
WITH TANK AND DRYER (DF)														
PASCAL 11-08-270 DF	V91TM92PWS380	270	11	15	1.65	99	58.2	8	116	69	3/4"	352	776	155 x 70 x 153
PASCAL 11-10-270 DF	V91TX92PWS380	270	11	15	1.50	90	53	10	145	69	3/4"	352	776	155 x 70 x 153
PASCAL 11-13-270 DF	V91TN92PWS380	270	11	15	1.15	69	40.6	13	188	69	3/4"	380	838	155 x 70 x 153
PASCAL 11-08-500 DF	V83TM92PWS380	500	11	15	1.65	99	58.2	8	116	69	3/4"	454	1001	200 x 70 x 165
PASCAL 11-10-500 DF	V83TX92PWS380	500	11	15	1.50	90	53	10	145	69	3/4"	454	1001	200 x 70 x 165
PASCAL 11-13-500 DF	V83TN92PWS380	500	11	15	1.10	66	38.83	13	188	69	3/4"	487	1074	200 x 70 x 165
PASCAL 15-08-270 DF	V91TY92PWS380	270	15	20	2.15	129	75.9	8	116	70	3/4"	362	798	155 x 70 x 153
PASCAL 15-10-270 DF	V91TZ92PWS380	270	15	20	1.85	111	65.3	10	145	70	3/4"	362	798	155 x 70 x 153
PASCAL 15-13-270 DF	V91TP92PWS380	270	15	20	1.55	93	54.7	13	188	70	3/4"	390	860	155 x 70 x 153
PASCAL 15-08-500 DF	V83TY92PWS380	500	15	20	2.15	129	75.9	8	116	70	3/4"	465	1025	200 x 70 x 165
PASCAL 15-10-500 DF	V83TZ92PWS380	500	15	20	1.85	111	65.3	10	145	70	3/4"	465	1025	200 x 70 x 165
PASCAL 15-13-500 DF	V83TP92PWS380	500	15	20	1.55	93	54.7	10	145	70	3/4"	497	1096	200 x 70 x 165

Free air delivery as per ISO 1217 Annex C, at 7.5 - 9.5 - 12.5 bar at the compressor outlet. ± 3 dB (A) as PNEUROP/CAGI PN-NTC 2.3.